

	<b>BULLSEYE 3+</b>	<b>BULLSEYE 5+</b>	<b>BULLSEYE 6</b>	<b>BULLSEYE 5MC</b>
Beam Reception Angle:	360 degrees	360 degrees	360 degrees	360 degrees
Operating Reception Range: (Dependent on Laser)	Over 1500 ft 460 m	Over 1500 ft 460 m	Over 1500 ft 460 m	Over 1500 ft 460 m
Vertical Reception:	6.75 in 171 mm	6.75 in 171 mm	8.75 in 222 mm	6.75 in 171 mm
Accuracy: (Grading / Excavating)				
Set-Up			3/16 in / 1/4 in 5 mm / 6 mm	
Fine	3/16 in 5 mm	3/16 in / 1/2 in 5 mm / 12 mm	3/8 in / 1/2 in 10 mm / 12 mm	16 accuracy levels set with Control Box
Standard	1/2 in. 12 mm	3/8 in / 1.0 in 10 mm / 25 mm	3/4 in / 1.0 in 20 mm / 25 mm	
Wide	1-1/4 in 32 mm	3/4 in / 2.0 in 20 mm / 50 mm	1-1/2 in / 2.00 in 40 mm / 50 mm	0 in / 1-1/2 in 0 mm / 40 mm
Blade Tilt Indication:	No	Built In	No	No
Tilt Accuracy:		± 0.5°, ± 1.5°, ± 2.5°		
Plumb Indication:	No	Built In	Built In	No
Plumb Accuracy:		± 0.5°, ± 1.5°, ± 2.5°	± 2.5°	
Swing Range:				
ACE Mode			± 10° to ± 30°	
On Grade Locations:				
Center (Grading)	Yes	Yes	Yes	Yes
Offset (Excavation)	No	Yes	Yes	No
Green On Grade:	Yes	Yes	Yes	No
Display Output:	Bright / Dim	Bright / Dim	Bright / Dim / Off	Bright / Dim
Power:				
Alkaline (Standard)	4 x "C" cell	4 x "C" cell	4 x "C" cell	No
Nickel Metal Hydride	Factory Option	Factory Option	Factory Option	No
Power Cable, 10-30 V	Optional	Optional	Optional	Required
Battery Life - Alkaline:				
Dim	75 hrs	60 hrs	75 hrs	N/A
Bright	50 hrs	45 hrs	50 hrs	N/A
Battery Life - NiMH:				
Dim	50 hrs	45 hrs	55 hrs	N/A
Bright	40 hrs	30 hrs	40 hrs	N/A
Battery Recharge Time:	3-4 Hrs	3-4 Hrs	3-4 Hrs	N/A
Charge Status Indication:	Yes	Yes	Yes	N/A
Auto Shut Off:	75 minutes	75 minutes	75 minutes	N/A
Low Battery Indication:	Yes	Yes	Yes	No
Remote Display Option:	Yes	Yes	Yes	No
Automatic Control Option:	Yes	Yes	Yes	Yes
Clamp Range:	«———— 1.66 to 2.00 inch (42 - 50 mm) diameter round tube —————» «———— 1.50 inch (38 mm) square tube —————»			
Internal Shock Mounts:	Yes	Yes	Yes	Yes
Warranty:	2 Years	2 Years	2 Years	2 Years
Operating Temperature:	«———— -4° F to +140° F —————» «———— -20° C to +60° C —————»			
Shipping Size (In Carrying Case):	«———— 19 x 16 x 7 inch —————» «———— 483 x 406 x 178 mm —————»			
Shipping Weight:	12 lbs 5.4 kg	12 lbs 5.4 kg	12.5 lbs 5.7 kg	12 lbs 5.4 kg